


FEATURES:

- Easy to install and use
- Single or dual sided
- Easy adjustment of treatment width
- Watt density control
- Parallel opening
- Process control
- Cost efficient treatment process
- Safe and clean



FoamTEC

Corona Treatment of Foam & Board



PP board made of blended PP co-polymer has one major disadvantage - low surface energy, resulting in poor surface adhesion for water-based adhesives and inks. Corona treatment systems by Tantec significantly increase surface energy and improve adhesion.

To optimize treatment and minimize waste it is important that the entire board surface is treated. To achieve this result, it is necessary to have the corona discharge around the board's edge. Tantec solves this problem by increasing the thickness of the dielectricum layer, increasing the roller's longevity and allowing corona treatment to the board's edge.

Increasing the insulation thickness will even out the discharge and ensure uniform treatment of boards up to 50 mm in thickness.

The FoamTEC is available for single and dual sided treatment. Adjustable electrode which ensures max. flexibility. Electrode height adjustment with digital read-out.

When treating corrugated board, it is important to limit the treatment inside the cavities to avoid loss of power and creation of ozone. The Foam TEC with thick insulation of counter electrodes limits treatment inside the cavities..

Head Office

Tantec A/S
Industrivej 6
DK-6640 Lunderskov
(+45) 7558 5822

USA:

(+1) 630-351-1320

USA/California:

(+1) 714-729-3499

Mail:

sales@tantec.com

Web:

www.tantec.com

Easy to install and use

The system requires compressed air and electrical power.

Single or dual sided

Both single and dual sided treatment systems available.

Easy adjustment of treatment width

The stainless steel wire electrodes are easily adjusted in treatment width. This requires no change to the electrical power system.

Watt density control

In combination with the HV-X series power generator, the system will adjust the generator output power according to the line speed.

Parallel opening

A parallel sliding device with pneumatic cylinders or motor drive enables easy access to the treating area for cleaning and maintenance.

Process control

In combination with the HV-X series power generator and PLC units the system can be monitored and adjusted very easily.

Cost efficient treatment process

Only electrical power is needed to achieve the effective treatment of foam and board; typically systems run from 1-4 kW depending on width and speed.

Safe and clean

The system is equipped with safety switches and interlocks to ensure safe use. The ozone filter system eliminates the ozone generated during the process.

Technical Specifications	FoamTEC Plasma Treater
Mains power	3 Ph. 400 VAC or 230 VAC (others on request)
Treatment power	200-4000 Watts
Compressed air	5-6 bar dry & clean
Treatment area	Single or dual sided treatment. Max. 50 mm thick
Treatment width	10-3000 mm
Line speed	1-30 m/min (others on request)
Treatable materials	PP, PE, PVC, nylon, PC, PVR and others (non-conductive only)
Optional	Driven rollers for part movement
Control and connectivity	Complete with touch panel. (Standard - Proface)
Regulation compliance	CE - RoHS - WEEE