



FEATURES:

- Compact design
- Easily fitted to new or existing production lines
- Uniform surface treatment
- Good accessibility
- “Easy-Fit” interchangeable electrode system
- Available for single (CS) and double sided (CD) treatment
- Stainless steel backing roller



LabelTEC

Corona Treatment of Narrow Web

The purpose of surface treatment of polymer-based materials is to increase surface wettability through electrical discharge. The low surface energy of polymerbased substrates often leads to poor adhesion of inks, glues and coatings. To obtain optimum adhesion, it is necessary to increase the surface energy of the substrate to just above that of the material to be applied. Surface treatment with Corona results in improved surface adhesion properties.

LabelTEC is designed for the pretreatment of conductive and nonconductive narrow webs.

This type of system will treat either one or both sides of the web and will accommodate widths from 100-500 mm, running at production speeds of up to 150 m/min.

All materials used are resistant to corrosion and easy to maintain.

LabelTEC conforms with CE regulations.

Option: Opening electrode hood.

Head Office

Tantec A/S
Industrivej 6
DK-6640 Lunderskov
(+45) 7558 5822

USA:

(+1) 630-351-1320

USA/California:

(+1) 714-729-3499

Mail:

sales@tantec.com

Web:

www.tantec.com

Technical Specifications	LabelTEC
Power supply	115 or 230VAC – 50/60Hz
Output power	Choose from 200W / 1000W / 2000W
Output frequency	12 - 30 kHz
Mains cable	Supplied without mainsplug
Control interface	Connector supplied
Operator display	HMI Remote
Control modes	Operator selectable from: Constant power / Constant voltage / Watt density control (Watt/m ² /min)
Alarms	Both through digital and analogue control inputs
Control inputs	Operator selectable from: Power setting / Voltage setting / Watt density
Treatment width, mm	From 50 - 500 mm
Side for treatment	1 or 2 sides
Speeds	1 - 250 m/min.
Electrodes	Ceramic or metal